



# CXT 300

## MOBILE CONE CRUSHER

Built to be reliable in the toughest operating conditions, the CXT 300 delivers excellent productivity through long stroke and high speed in terms of capacity, reduction, and end product shape. The variable speed of crusher provides the ability to obtain the best combination of production and product shape, maximizing efficiency while the heavy duty main conveyor belt features a spring loaded adjustable belt scraper, self aligning belt rollers, and pressure monitoring sensor to detect blockages or stoppage.

The large high resolution control panel display with full machine monitoring and troubleshooting capabilities and simple hydraulic controls ensure ease of operation.

## Features & Benefits

- Powerful MC300 Cone
- Tracked
- Large gap between crusher discharge and main conveyor for enhanced material flow
- Integrated hopper with folding rear door for ease of loading
- Open chassis and unrivaled access from ground level for maintenance and service
- Less than 5 minutes from setup to operation



## PERFORMANCE SPECIFICATION\* \* Depending on application

Engine	Cone	Feed Opening	Feeder Belt Width
380 kW (510 Hp)	MC300	1050mm (41")	1200mm (48")
Hopper Volume	Crusher Drive	CSS Adjustment	Production Rate*
6.2m <sup>3</sup> (8.1yd <sup>3</sup> )	Direct Drive	Hydraulic	up to 250TPH

## DIMENSION SPECIFICATION\* \* Depending on material density and set-up

TRANSPORT DIMENSIONS		
Height	Width	Length
3.6m (11' - 9.7")	3.15m (10' - 4")	17.5m (57' - 4")
MAX WORKING DIMENSIONS		CRUSHING CHAMBER
Stockpile Height	Belt Width	Max. Feed Opening
3887mm (12' - 9")	1200mm (48")	211mm (8.31")